

DRAG RACING - BIAS

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND(S) | TUBE ID |
|-----------------------------|---------------------|----------------|-------------|--------------|---------------|------------------|--------------------|---------------|----------------|---------|
| DRAG FRONT | | | | | | | | | | |
| 18085 | 23.0X 5.0-15 | Drag Front | 4.8" | 23.0" | 72.0" | 3.5-4.0" | 3.5" | 5.5" | Drag Front | |
| 18095 | 24.0X 5.0-15 | Drag Front | 4.8" | 23.8" | 75.0" | 3.5-4.0" | 3.5" | 5.8" | Drag Front | |
| 18100 | 25.0X 4.5-15 PRO | Drag Front | 4.5" | 25.0" | 78.0" | 3.5-4.0" | 3.5" | 5.75" | Drag Front | |
| 18102 | 25.0X 5.0-15 | Drag Front | 4.8" | 24.8" | 77.9" | 3.5-4.0" | 3.5" | 6.3" | Drag Front | |
| 18103 | 26.0X 4.5-17 | Drag Front | 4.5" | 26.3" | 82.0" | 3.5-4.5" | 4.5" | 5.8" | Drag Front | |
| 18105 | 26.0X 4.5-15 | Drag Front | 4.3" | 25.8" | 81.0" | 3.5-4.0" | 3.5" | 6.0" | Drag Front | |
| 18106 | 27.0X 4.5-15 | Drag Front | 4.5" | 27.0" | 85.0" | 3.5-4.0" | 4.0" | 6.8" | Drag Front | |
| 18107 | 28.0X 4.5-15 | Drag Front | 4.5" | 27.7" | 87.0" | 3.5-4.0" | 4.0" | 7.5" | Drag Front | |
| 18108 | 22.0X 2.5-17 | Dragster Front | 1.5" | 22.0" | 69.0" | 2.5" | 2.5" | 2.7" | Dragster Front | |
| 18109 | 27.5X 4.5-17 | Drag Front | 4.8" | 27.6" | 86.5" | 3.5-4.5" | 4.5" | 7.5" | Drag Front | |
| 18112 | 28.0X 4.5-18 | Drag Front | 4.5" | 28.0" | 88.5" | 3.5"-5.0" | 5.0" | 7.25" | Drag Front | |
| DRIVE TIRES - SLICKS | | | | | | | | | | |
| 18060 | 24.5/ 8.0-13 | Drag Slick | 7.8" | 24.3" | 76.0" | 6-8" | 7" | 9.0" | D06 | A |
| 18110 | 26.0/ 8.0-15 | Drag Slick | 8.0" | 26.1" | 82.0" | 7-8" | 8" | 9.7" | D06 | A |
| 18115 | 26.0/ 8.5-15* | Drag Slick | 9.0" | 26.1" | 82.0" | 7-8" | 8" | 10.3" | C11 | A |
| 18120 | 26.0/ 9.0-15 | Drag Slick | 9.0" | 26.1" | 82.0" | 7-8" | 8" | 10.5" | D06 | A |
| 18131 | 26.0/10.0-15 | Drag Slick | 10.0" | 26.2" | 82.0" | 8-10" | 9" | 11.0" | D06 | A |
| 18140 | 28.0/ 9.0-15 | Drag Slick | 9.0" | 28.0" | 88.0" | 8-10" | 8" | 11.1" | D06 | A |
| 18150 | 28.0/10.0-15 | Drag Slick | 10.0" | 28.0" | 88.0" | 8-10" | 8" | 11.3" | D06 | A |
| 18153 | 28.0/10.0-16 | Drag Slick | 10.0" | 28.0" | 88.0" | 8-10" | 10" | 12.0" | C07 | A |
| 18154 | 28.0/10.5-15* | Drag Slick | 10.2" | 28.0" | 88.0" | 8-10" | 10" | 12.5" | D05 | A |
| 18155 | 28.0/10.5-15* | Drag Slick | 10.2" | 28.0" | 88.0" | 8-10" | 10" | 12.3" | C07 | A |
| 18156 | 28.0/10.5-15W | Drag Slick | 10.9" | 28.0" | 88.0" | 10-12" | 10" | 13.1" | C07 | A |
| 18157 | 28.0/10.0-17 | Drag Slick | 9.5" | 28.0" | 88.0" | 8-10" | 8" | 10.3" | D06 | D |
| 18158 | 28.0/10.0-18 | Drag Slick | 9.5" | 28.0" | 88.0" | 8-10" | 10" | 11.0" | D06 | D |
| 18160 | 29.0/ 9.0-15 | Drag Slick | 9.0" | 29.1" | 91.5" | 8-10" | 8" | 11.3" | D06, D07 | B |
| 18170 | 29.0/10.0-15 | Drag Slick | 10.0" | 29.1" | 91.5" | 8-10" | 8" | 11.9" | D06 | B |
| 18175 | 29.0/10.5-15 W* | Drag Slick | 11.0" | 29.3" | 92.0" | 8-10" | 10" | 13.0" | D06 | B |
| 18180 | 29.0/11.0-15 | Drag Slick | 11.0" | 29.3" | 92.0" | 8-10" | 10" | 13.2" | D06 | B |
| 18190 | 29.0/12.0-15 | Drag Slick | 12.0" | 29.3" | 92.0" | 10-12" | 10" | 13.7" | D06 | B |
| 18192 | 29.5/10.5-15 | Drag Slick | 11.1" | 30.6" | 96.0" | 10-12" | 10" | 13.2" | D06 | B |
| 18194 | 29.5/10.5S-15* | Drag Slick | 10.5" | 29.5" | 94.0" | 8-10" | 10" | 13.3" | C06 | B |
| 18195 | 29.5/11.5-15 W* | Drag Slick | 13.5" | 30.6" | 96.0" | 12-14" | 12" | 15.0" | D06 | B |
| 18200 | 30.0/ 9.0-15 | Drag Slick | 9.0" | 30.0" | 94.0" | 8-10" | 8" | 11.5" | D05, D07 | B |
| 18205 | 30.0/10.5-15 | Drag Slick | 10.5" | 30.0" | 94.0" | 8-10" | 10" | 13.3" | D05 | B |
| 18220 | 30.5/10.5-15 | Drag Slick | 10.5" | 30.5" | 97.0" | 10-12" | 12" | 14.5" | C07 | B |
| 18235 | 31.5/12.5-15 W* | Drag Slick | 13.5" | 31.7" | 99.5" | 12-14" | 14" | 17.0" | D05 | B |
| 18237 | 13.5/31.5-15L*** | Drag Slick | 13.5" | 31.7" | 99.5" | 12-14" | 14" | 17.2" | C07 | B |
| 18240 | 31.0/14.0-15 | Drag Slick | 14.0" | 31.2" | 98.0" | 12-14" | 12" | 16.5" | D05 | C |
| 18242 | 32.0/12.0-15 | Drag Slick | 12.2" | 32.0" | 101.0" | 10-12" | 12" | 16.0" | D05 | C |
| 18243 | 32.0/13.0-15 | Drag Slick | 13.2" | 32.0" | 101.0" | 12-13" | 12" | 16.5" | D05 | C |
| 18245 | 32.0/13.5-15 W* | Drag Slick | 14.0" | 32.3" | 102.0" | 12-14" | 14" | 17.5" | D05 | C |
| 18250 | 32.0/14.0-15 | Drag Slick | 14.0" | 32.3" | 102.0" | 12-14" | 14" | 17.5" | D05 | C |
| 18255 | 14.0/32.0-15 L*** | Drag Slick | 14.0" | 32.3" | 102.0" | 12-14" | 14" | 17.5" | C07 | C |
| 18260 | 32.0/14.5-15 W* | Drag Slick | 15.0" | 32.6" | 102.5" | 14-15" | 14" | 18.0" | D05 | C |
| 18265 | 14.5/32.0-15 L*** | Drag Slick | 15.0" | 32.3" | 102.0" | 14-15" | 14" | 18.0" | C07 | C |
| 18300 | 32.5/16.5-15* | Drag Slick | 16.7" | 32.3" | 101.5" | 15-16" | 15" | 19.5" | C07 | C |
| 18332 | 33.0/10.5-15 Outlaw | Drag Slick | 10.8" | 33.0" | 104.0" | 10-12" | 12" | 15.5" | C11 | C |
| 18336 | 33.0/10.5W-16 | Drag Slick | 11.3" | 33.0" | 104.0" | 16" | 16" | 17.3" | C11 | C |
| 18350 | 33.0/12.0-15 | Drag Slick | 12.2" | 33.0" | 102.0" | 10-12" | 10" | 15.3" | C09 | C |
| 18355 | 33.0/13.0-15 | Drag Slick | 13.2" | 33.0" | 102.0" | 12-13" | 12" | 16.7" | C06 | C |
| 18367 | 14.5/33.0-15 L*** | Drag Slick | 14.5" | 33.0" | 104.0" | 14-16" | 14" | 17.8" | C07 | C |
| 18370 | 33.0/15.0-15 | Drag Slick | 15.0" | 33.0" | 104.0" | 14-15" | 14" | 18.3" | D05 | C |
| 18372 | 33.0/15.0S-15* | Drag Slick | 15.0" | 33.0" | 104.0" | 14-15" | 15" | 18.5" | D06 | C |
| 18400 | 33.0/16.0-15* | Drag Slick | 17.0" | 33.0" | 104.0" | 15-16" | 15" | 19.8" | D05, D06, C07 | C |
| 18450 | 33.0/16.5-15 S** | Drag Slick | 17.0" | 33.0" | 104.0" | 15-16" | 15" | 19.8" | D06 | C |

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

DRAG RACING - BIAS CONTINUED

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND(S) | TUBE ID |
|-------------|---------------|---------------|-------------|--------------|---------------|------------------|----------------------|---------------|--------------|---------|
| 18500 | 33.0/17.0-16* | Drag Slick | 17.0" | 33.0" | 104.0" | 15-16" | 15" | 19.8" | C07 | C |
| 18600 | 33.5/16.0-15* | Drag Slick | 17.0" | 33.6" | 106.0" | 15-16" | 15" | 19.5" | C07 | C |
| 18650 | 33.5/17.0-16* | Drag Slick | 17.0" | 33.6" | 106.0" | 15-16" | 16" | 19.5" | C07 | C |
| 18700 | 33.5/17.0-16 | Drag Slick | 17.0" | 33.6" | 106.0" | 15-16" | 16" | 20.3" | C06 | A* |
| 18705 | 33.5/17.0-16 | Drag Slick | 17.0" | 33.6" | 106.0" | 15-16" | 16" | 20.3" | C35 | A* |
| 18740 | 34.0/14.0-16 | Drag Slick | 14.0" | 34.0" | 108.0" | 13-16" | *16"(*Beadlock Only) | 18.3" | C1350 | |
| 18750 | 35.0/15.0-16 | Drag Slick | 15.0" | 35.0" | 110.0" | 14-16" | 16" | 18.6" | C1450 | |
| 18760 | 14.0/35.0-16 | Drag Slick | 14.0" | 35.0" | 110.0" | 15-16" | 16" | 19.2" | BR3 | |
| 18770 | 15.0/34.5-16 | Drag Slick | 15.0" | 35.0" | 110.0" | 15-16" | 16" | 19.5" | C1550 | |
| 18780 | 17.0/34.5-16 | Drag Slick | 17.0" | 35.0" | 110.0" | 15-16" | 16" | 20.0" | C2055, N2021 | A* |
| 18790 | 34.5/17.0-16 | Drag Slick | 17.0" | 35.0" | 110.0" | 15-16" | 16" | 21.0" | W2021 | A* |
| 18910 | 17.0/36.0-16 | Drag Slick | 17.0" | 36.2" | 112.5" | 15-16" | 16" | 20.5" | C2021, C2055 | A* |
| 18950 | 7.0/29.0-15 | Drag Master | 7.0" | 29.0" | 91.0" | 6-8" | 7" | 10.4" | DRAG | A |

*STIFF SIDEWALL - **SOFT SIDEWALL - ***LIGHTWEIGHT

| SOFT | | | COMPOUND | | | | | | | FIRM | |
|--------------|-----|-----|----------|-----|-----|-----|------|----------------------|------------|------|--|
| PRO 8, 9, 10 | DBR | DR2 | C06 | BR3 | C07 | C11 | DRAG | C1550/C2055 | Drag Front | | |
| D05 | D06 | D06 | C35 | C09 | | | | D07C2021/N2021/W2021 | | | |

DRAGSTER FRONT



DRAG SLICK



DRAG MASTER



DRAG RACING - RADIAL

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND(S) |
|-------------|-------------------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|-------------|
| 18198 | 29.5/10.5R-15 Radial*** | Drag Slick | 10.5" | 29.9" | 94.0" | 8-10" | 10" | 12.5" | C06 |
| 18209 | 30.0/ 9.0R-15 Radial*** | Drag Slick | 9.0" | 29.5" | 92.5" | 8-10" | 8" | 11.0" | C06 |
| 18210 | 30.0/ 9.0R-15 Radial | Drag Slick | 9.0" | 29.5" | 92.5" | 8-10" | 8" | 11.0" | C07 |
| 18212 | 9.0/30.0R-15 Radial*** | Drag Slick | 9.0" | 29.9" | 94.0" | 8-10" | 8" | 11.0" | C06 |
| 18213 | 9.0/30.0R-15 Radial*** | Drag Slick | 9.9" | 30.0" | 94.0" | 9-10" | 10" | 12.2" | C30 |
| 18214 | 30.0/10.5R-15 Radial*** | Drag Slick | 10.5" | 29.5" | 92.5" | 9-10" | 10" | 12.5" | C06 |
| 18215 | 30.0/10.5R-15 Radial | Drag Slick | 10.5" | 29.5" | 92.5" | 9-10" | 10" | 12.5" | C07 |
| 18239 | 31.5/13.5R-15 Radial | Drag Slick | 13.5" | 31.8" | 99.7" | 14-15" | 14" | 16.3" | C06 |
| 18247 | 32.0/13.5R-15 Radial | Drag Slick | 13.5" | 32.2" | 101.5" | 14-15" | 14" | 16.8" | C06 |



DRAG BRACKET RADIAL CONTINUED

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND(S) |
|-------------|---------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|-------------|
| 18805DBR | 26.0/8.5 R15 | Drag Slick | 8.5" | 26.2" | 82.5" | 8-9" | 8.0" | 10.2" | DBR |
| 18810DBR | 26.0/10.0 R15 | Drag Slick | 10.5" | 26.2" | 82.5" | 9-11" | 9.0" | 11.7" | DBR |
| 18815DBR | 28.0/ 9.0 R15 | Drag Slick | 9.5" | 28.0" | 88.25" | 8-10" | 8.0" | 11.1" | DBR |
| 18820DBR | 28.0/10.5 R15 | Drag Slick | 10.5" | 28.0" | 88.5" | 10-12" | 10.0" | 12.7" | DBR |
| 18825DBR | 28.0/10.5 R17 | Drag Slick | 10.5" | 28.0" | 88.5" | 10-11" | 10.0" | 11.5" | DBR |
| 18830DBR | 28.0/10.5 R18 | Drag Slick | 10.5" | 28.0" | 88.5" | 10-11" | 10.0" | 11.5" | DBR |
| 18835DBR | 29.5/10.5 R15 | Drag Slick | 10.5" | 29.5" | 93.5" | 9.5-12" | 10.0" | 13.2" | DBR |
| 18837DBR | 29.5/10.5 R17 | Drag Slick | 10.9" | 29.8" | 93.9" | 9.5-12" | 9.5" | 12.1" | DBR |
| 18840DBR | 29.5/10.5 R18 | Drag Slick | 10.5" | 29.5" | 93.5" | 9.5-12" | 10.0" | 13.2" | DBR |
| 18845DBR | 29.5/11.5 R18 | Drag Slick | 11.6" | 29.8" | 93.8" | 10-12" | 11.0" | 13.3" | DBR |
| 18850DBR | 29.5/11.5 R20 | Drag Slick | 11.6" | 29.9" | 93.9" | 10-12" | 11.0" | 12.9" | DBR |
| 18860DBR | 31.0/11.5 R15 | Drag Slick | 11.5" | 31.4" | 98.75" | 12-14" | 14.0" | 16.0" | DBR |

DRAG SLICK



JR DRAGSTER

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND |
|-------------|--------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|---------------|
| 18010 | 16.0/ 1.5-12 | Jr. Front | 1.0" | 16.0" | 50.0" | 1.0-1.5" | 1.5" | 1.7" | TUBE REQUIRED |
| 18031 | 18.0/ 8.0-8 | Drag Slick | 7.7" | 17.7" | 55.0" | 7-8" | 8" | 9.9" | PRO 8 |
| 18036 | 18.0/ 9.0-8 | Drag Slick | 8.5" | 17.7" | 55.5" | 8-9" | 8" | 10.25" | PRO 9 |
| 18041 | 18.0/10.0-8 | Drag Slick | 9.5" | 17.7" | 55.0" | 8-10" | 8" | 10.6" | PRO10 |

*Tube required Summit JRC-654-431 or JEGS 574-654-438

JR FRONT



DRAG SLICK



D.O.T. DRAG - RADIAL

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND |
|-------------|------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|----------|
| 17310DR2 | P225/50R15 | DR2 | 8.5" | 23.9" | 75.2" | 7-9" | 7" | 9.5" | DR2 |
| 17313DR2 | P295/55R15 | DR2 | 11.0" | 27.6" | 86.7" | 8-10" | 9.5" | 12.5" | DR2 |
| 17314DR2 | P235/60R15 | DR2 | 8.4" | 26.2" | 82.3" | 7-9" | 7" | 10.0" | DR2 |
| 17315DR2 | P275/50R15 | DR2 | 9.5" | 25.6" | 80.5" | 8-10" | 8.5" | 10.8" | DR2 |
| 17316DR2 | P295/65R15 | DR2 | 10.0" | 30.0" | 94.5" | 8-10" | 8.5" | 12.0" | DR2 |
| 17317 | P275/60R15 | DOT | 9.8" | 27.7" | 87.0" | 8-10" | 8" | 11.5" | DOT |
| 17318DR2 | P325/50R15 | DR2 | 11.75" | 27.7" | 87.0" | 9-11" | 10" | 13.5" | DR2 |
| 17320DR2 | P225/50R16 | DR2 | 8.4" | 24.9" | 78.2" | 7-9" | 7" | 9.3" | DR2 |
| 17325DR2 | P255/50R16 | DR2 | 9.3" | 26.1" | 82.0" | 8-10" | 8" | 10.7" | DR2 |

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.

D.O.T. DRAG - RADIAL CONTINUED

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | COMPOUND |
|-------------|------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|----------|
| 17326DR2 | P295/50R16 | DR2 | 10.5" | 27.7" | 87.0" | 8-10" | 9" | 12.7" | DR2 |
| 17327DR2 | P225/45R17 | DR2 | 8.3" | 24.9" | 78.3" | 7-8.5" | 8" | 9.7" | DR2 |
| 17328DR2 | P245/45R17 | DR2 | 9.2" | 26.0" | 81.7" | 7.5-9" | 8" | 10.0" | DR2 |
| 17330DR2 | P275/40R17 | DR2 | 10.0" | 25.8" | 81.0" | 9-11" | 10" | 11.0" | DR2 |
| 17332DR2 | P315/35R17 | DR2 | 11.5" | 25.9" | 81.3" | 9-11" | 11" | 12.6" | DR2 |
| 17335DR2 | P335/35R17 | DR2 | 12.0" | 25.9" | 81.3" | 11-13" | 12" | 13.5" | DR2 |
| 17340DR2 | P245/40R18 | DR2 | 8.8" | 26.0" | 81.5" | 7-9" | 9" | 10.3" | DR2 |
| 17342DR2 | P315/30R18 | DR2 | 11.0" | 26.0" | 81.5" | 11-12" | 11" | 12.5" | DR2 |
| 17343DR2 | P325/45R18 | DR2 | 10.6" | 30.2" | 94.3" | 10-12" | 11" | 13.1" | DR2 |
| 17345DR2 | P335/30R18 | DR2 | 12.2" | 25.9" | 81.3" | 12-13" | 12" | 13.4" | DR2 |
| 17375DR2 | P275/60R15 | DR2 | 10.0" | 28.0" | 88.8" | 8-10" | 10" | 12.7" | DR2 |

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for racing and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible **SERIOUS PERSONAL INJURY OR DEATH**.



QUICK TIME PRO D.O.T.

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | TUBE ID |
|-------------|------------------|----------------|-------------|--------------|---------------|------------------|--------------------|---------------|---------|
| 17415 | 26 x 9.50-15 LT | Quick Time Pro | 8.0" | 26.1" | 82.0" | 6-8" | 8" | 10.0" | A |
| 17421 | 26 x 11.50-15 LT | Quick Time Pro | 10.0" | 26.1" | 82.0" | 8-10" | 8" | 10.8" | A |
| 17431 | 26 x 9.50-16 LT | Quick Time Pro | 8.0" | 26.1" | 82.0" | 6-8" | 8" | 9.3" | A |
| 17500 | 27 x 10.50-15 LT | Quick Time Pro | 9.0" | 27.1" | 85.0" | 8-10" | 8" | 10.5" | A |
| 17510 | 27 x 11.50-15 LT | Quick Time Pro | 10.0" | 27.1" | 85.0" | 8-10" | 8" | 11.3" | A |
| 17601 | 28 x 11.50-15 LT | Quick Time Pro | 10.0" | 27.9" | 87.5" | 8-10" | 8" | 11.2" | A |
| 17604 | 28 x 11.50-17 LT | Quick Time Pro | 9.75" | 28.5" | 89.0" | 8-10" | 10" | 13.1" | D |
| 17606 | 28 x 13.50-15 LT | Quick Time Pro | 11.0" | 27.8" | 87.3" | 10-12" | 10" | 12.8" | A |
| 17611 | 28 x 14.50-15 LT | Quick Time Pro | 12.0" | 27.7" | 87.0" | 10-12" | 10" | 13.3" | A |
| 17652 | 28 x 14.50-17 LT | Quick Time Pro | 11.75" | 28.5" | 89.0" | 10-12" | 11" | 13.5" | A |
| 17702 | 29 x 12.50-15 LT | Quick Time Pro | 10.0" | 29.0" | 91.0" | 8-10" | 10" | 12.8" | B |
| 17705 | 29 x 13.50-15 LT | Quick Time Pro | 11.0" | 29.0" | 91.0" | 10-12" | 10" | 13.3" | B |
| 17710 | 29 x 14.50-15 LT | Quick Time Pro | 12.0" | 29.2" | 91.8" | 10-12" | 10" | 13.8" | B |
| 17795 | 31 x 14.50-15 LT | Quick Time Pro | 11.0" | 30.6" | 96.0" | 10-12" | 10" | 14.3" | C |
| 17800 | 31 x 16.50-15 LT | Quick Time Pro | 13.1" | 30.9" | 97.0" | 12-14" | 12" | 15.8" | C |
| 17810 | 31 x 18.50-15 LT | Quick Time Pro | 15.0" | 30.9" | 97.0" | 14-15" | 14" | 17.8" | C |
| 17900 | 33 x 18.50-15 LT | Quick Time Pro | 15.0" | 33.0" | 103.5" | 14-15" | 14" | 18.5" | C |
| 17910 | 33 x 22.50-15 LT | Quick Time Pro | 17.0" | 33.4" | 105.0" | 15-16" | 15" | 19.3" | C |



WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for making and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible **SERIOUS PERSONAL INJURY OR DEATH**.



QUICK TIME D.O.T.

| ITEM NUMBER | TIRE SIZE | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | TUBE ID |
|-------------|------------------|------------------|-------------|--------------|---------------|------------------|--------------------|---------------|---------|
| 17050 | P245/60D-15 | Super Chain Link | 8.0" | 26.2" | 82.3" | 6-8" | 8" | 10.2" | A |
| 17110 | P275-60D-15 | Super Chain Link | 9.0" | 27.3" | 85.8" | 8-10" | 8" | 11.3" | A |
| 17125 | P295/60D-15 | Super Chain Link | 10.0" | 29.6" | 93.0" | 8-10" | 8" | 12.0" | B |
| 17130 | P325/50D-15 | Super Chain Link | 10.5" | 28.1" | 88.3" | 8-10" | 8" | 12.5" | A |
| 17140 | 31 x 16.50-15 LT | Super Chain Link | 14.0" | 30.7" | 96.5" | 12-14" | 14" | 17.8" | B |
| 17150 | 31 x 18.50-15 LT | Super Chain Link | 15.0" | 31.1" | 97.5" | 14-15" | 14" | 18.0" | C |

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for racing and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible **SERIOUS PERSONAL INJURY OR DEATH**.

SUPER CHAIN LINK



RACING TUBES & LINER

| ITEM NUMBER | TUBE SIZE | | TREAD WIDTH | TUBE ID |
|-------------|------------------|--|-------------|---------|
| 288088-15 | 80/ 88-15 TUBE | WILL FIT 80" TO 88" CIRC. | 6" TO 11" | A |
| 288088-17 | 80/ 88-17 TUBE | WILL FIT 80" TO 88" CIRC. | 6" TO 11" | D |
| 2886100-15 | 86/100-15 TUBE | WILL FIT 86" TO 100" CIRC. | 11" TO 13" | B |
| 2894106-15 | 94/106-15 TUBE | WILL FIT 94" TO 106" CIRC. | 15" TO 19" | C |
| 32401 | 75/16.0-16 LINER | FOR USE WITH ITEM NUMBERS 18780, 18790 & 18910 | | A* |

PRO STREET D.O.T. - RADIALS

| ITEM NUMBER | TIRE SIZE | SPEED RATING | TREAD PATTERN | TREAD WIDTH | APPROX. DIA. | APPROX. CIRC. | RECOM. RIM WIDTH | MEASURED RIM WIDTH | SECTION WIDTH | MAX LOAD | RATED INF. PSI | LOAD RANGE |
|--------------|-------------------|--------------|---------------|-------------|--------------|---------------|------------------|--------------------|---------------|----------|----------------|------------|
| FRONT | | | | | | | | | | | | |
| 19030 | 24 x 7.50R-15 LT | 71H | Pro Street | 5.3" | 23.2" | 72.8" | 5.5-7.0" | 6.0" | 7.5" | 760 | 35 | B |
| 19040 | 25 x 7.50R-15 LT | 75H | Pro Street | 5.3" | 24.3" | 76.4" | 5.5-7.0" | 6.0" | 7.5" | 855 | 35 | B |
| 19050 | 26 x 7.50R-15 LT | 79H | Pro Street | 5.3" | 25.3" | 80.3" | 5.5-7.0" | 6.0" | 7.5" | 965 | 35 | B |
| 19055 | 26 x 7.50R-17 LT | 74H | Pro Street | 5.3" | 25.4" | 80.4" | 5.5-7.0" | 6.0" | 7.5" | 825 | 35 | B |
| 19070 | 27 x 9.50R-15 LT | 90H | Pro Street | 8.0" | 26.5" | 84.0" | 6.5-8.5" | 8.0" | 10.0" | 1325 | 35 | B |
| 19075 | 27 x 10.50R-15 LT | 88H | Pro Street | 8.3" | 26.1" | 82.4" | 7-9.0" | 8.5" | 10.5" | 1235 | 35 | B |
| 19155 | 29 x 12.50R-15 LT | 97H | Pro Street | 10.2" | 29.1" | 91.5" | 9.0-11.5" | 10.0" | 13.0" | 1610 | 35 | C |
| 19200 | 29 x 15.50R-15 LT | 99H | Pro Street | 12.1" | 28.7" | 91.5" | 11-14" | 12.0" | 15.3" | 1710 | 35 | C |
| 19250 | 29 x 18.50R-15 LT | 101H | Pro Street | 14.6" | 28.4" | 90.8" | 13-16.5" | 14.0" | 18.0" | 1820 | 35 | C |
| 19275 | 31 x 12.50R-15 LT | 103H | Pro Street | 10.3" | 30.5" | 96.0" | 9.0-11.5" | 10.0" | 13.5" | 1930 | 35 | C |
| 19276 | 31 x 12.50R-16 LT | 101H | Pro Street | 10.3" | 30.5" | 96.0" | 9.0-11.5" | 10.0" | 12.8" | 1820 | 35 | C |
| 19300 | 31 x 16.50R-15 LT | 106H | Pro Street | 12.8" | 30.6" | 96.2" | 11.5-15" | 12.0" | 16.0" | 2095 | 35 | C |
| 19350 | 31 x 18.50R-15 LT | 108H | Pro Street | 14.5" | 30.6" | 96.2" | 13-16.5" | 14.0" | 18.0" | 2205 | 35 | C |
| 19390 | 32 x 21.50R-15 LT | 115H | Pro Street | 16.8" | 31.7" | 100.0" | 15-19.5" | 17.0" | 21.5" | 2680 | 35 | C |

WARNING: "Pro Street Tires are designed for highway use and are not suitable for racing purposes."

NOTE: H Speed Rating = 130 mph/210 km/h.

PRO STREET



REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES. FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.