## **HOOSIER RACING TIRE**



65465 SR 931 • LAKEVILLE, INDIANA 46536 Phone (574) 784-3152 • Fax (574) 784-2385 www.hoosiertire.com

## TIRES DESIGNED FOR CHAMPIONS

Product Bulletin 05/10/24



## Hoosier Adds New Bracket Dragster/Top Dragster Tire 18750C1450

**LAKEVILLE, IND.** – Hoosier has introduced a new addition to its impressive line-up of tires, the 35.0/15.0-16 C1450. This tire is specifically designed for drag racing in the Bracket Dragster and Top Dragster segments. The tire compound is formulated to offer consistency and repeatability in all racing conditions. For optimum performance, it is recommended to use rims that are 15 inches or narrower. If the rim width exceeds 15 inches, the tire must be mounted on a bead lock wheel. The starting air pressure should range from 5.0 psi to 5.5 psi.

Small to medium burnout.

Item Number	Tire Size	Tread Width	Approx. Dia.	Approx. Circ.	Recom. Rim Width	Section Width	Compound
18750	35.0/15.0-16	15.0"	35.0"	110.0"	16"	18.6"	C1450

For more information or to place an order, please contact your nearest Hoosier Racing Tire Distributor. A complete list of locations can be found on our website, <a href="https://www.hoosiertire.com">www.hoosiertire.com</a>.