UTV / SxS										
ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND COMPARISON SOFT TO FIRM	APPLICATION
16105	21.0x6.0-10	RIB	7.0"	21.0″	66.0"	6-8"	7″	8.25"	S500, H500	RZR 170
16400	27.5/8.0-15	Super Chain Link	8.0″	27.75"	87.0"	7-8"	8″	10.5″	S500, M500	Prod 1000/PS
16450	27.5/8.0-15	Super Chain Link	8.75″	27.75"	87.0"	7-9"	8″	11.3″	S500, M500	Turbo 1000/PM
16470	27.0/9.0-15	Knobby	9.0"	27.0"	84.25"	7-8"	8″	9.75″	M550	Short Course
16510	30.0/10.0-15	Knobby	10.0"	30.0"	92.5"	7-8"	8″	10.25″	M550	Short Course
SOFT								FIRM		
	D10	RD12		D12	RD15	RD20	RD30			
	D10A				S50	D20A T10	D30A M: T20		MX200 XC200 T30	H500

WARNING: Not For recreational use. Hoosier ATV Tires are designed and manufacture d for racing purpose only. Within a Closed course for organized competitions. The prohibited use of Hoosier Racing tires on public road ways may result in loss of traction, unexpected loss of traction, unexpected loss of the local control, or sudden loss of tire pressure, resulting in a vehicle crash and the local control of the local controlpossible SERIOUS PERSONAL INJURY OR DEATH.

